


# Installation Example

## Concrete Class A 15 - F 900



\*  $y \geq$  Channel height - 14 cm

Category according to EN 1433 / DIN 19580		A 15	B 125	C 250	D 400**	E 600**	F 900**	Applying to following systems: <b>FASERFIX SUPER 100, 150, 200, 300, 400, 500</b> <b>SERVICE CHANNEL FASERFIX SUPER 150, 200, 300, 400, 500</b>	
Foundation: width x / height y / thickness z (in cm)		10 /* / 10	10 /* / 10	15 /* / 15	15 /* / 15	15 /* / 20	15 /* / 20		
EN 206-1 / DIN 1045-2 The named concrete quality is a minimum quality	quality of concrete stretcher								
	without danger of frost on the lateral support	C25/30 X0							
	with danger of frost on the lateral support	C25/30 XF3							
The installation examples / advise constantly are adapted to the technical conditions. With new editions older expenditures lose their validity. Before planning or installation please verify the current version at <a href="http://www.hauraton.com">www.hauraton.com</a> In building construction is a sealing layer below the channels necessary.								Date: 01.03.2023	Our general installation instructions apply.
The installation example represents a proven recommendation from HAURATON. The final responsibility for the execution lies with the planner in charge. Specific conditions of the project must be taken into account.								Format DIN A4	
** Installation situations of drainage systems with high dynamic loads (e.g. airports, motorways and manoeuvring areas of buses, lorries and forklifts, etc.) are not sufficiently considered in DIN EN 1433. Please contact us for such applications to work out project-specific solutions.								scale 1:6	
0000023712_BRITISH.dwg								21	EBBw
FF-S-200 Typ 010 Rinnenunterteil Einbaubeispiel Klasse E 600 in Beton									